

MODEL NUMBER: Braille SKU #B2015
 Model Name: 15lb All-Season Battery



PERFORMANCE

Voltage:	12 volts
Full Charge Voltage:	13.8 volts
Short Circuit Current (Max Cranking Amps):	2500
Pulse Cranking Amps (PCA) 5 sec @ 80F:	1067
Pulse Cranking Amps (PCA) 10 sec @ 80F:	933
Pulse Cranking Amps (PCA) 20 sec @ 80F:	824
Cranking Amps 30 sec @ 80F:	690
Cranking Amps 30 sec @ 32F:	574
Cold Cranking Amps 30 sec @ 0F:	425
Reserve Capacity:	35 minutes
Capacity (C/20 rate):	21 amp hr
Internal Resistance (ohms):	4.5 milliohms (.0045ohms)
Life Cycle @ 10% DOD:	3100 cycles

PHYSICAL SPECS

Unique Features:	Durable Virgin Poly Casing, Horizontal and Vertical Mounting
BCI Group:	Usable for all Group Sizes
Length:	6.8"
Width:	3.3"
Height (no posts):	6.1"
Minimum Weight (lbs):	15 lbs
Post Type:	SAE Automotive Posts included & 6 x 1.0mm racing bolts included.
Stainless Stud:	Both Automotive SAE Posts and Race Style Bolts are Stainless with a 6 x 1.0mm bolt pitch
Recommended Mounts:	<i>Vertical:</i> BRBUMKAL; B2015ALMK; BRBUMKFRP8; <i>Horizontal:</i> B2015ALMK; BRBUMKFRP6

CHARGING INFORMATION

Recommended charging information:	Braille Electronic Charger
Alternator:	Automotive, Marine and Cycle Compatible
Battery charger:	Braille Model B12V2AHEBC
Rapid Recharge:	Yes, 10-20 amp/hr electronically controlled
Maximum charge current:	40 amp/hr for 15 min
Maximum recharge Voltage @70F:	14.45 – 14.75 volts
Float charge @ 70F:	13.4 volts - 13.7 volts

PRICE & WARRANTY

MSRP:	\$159.99
Warranty:	2 year pro-rated, 1yr free replacement for street and competition purposes.