

sector 111

AP Racing Brakes

Rev. A

Page 1 of 22

Assembly Step

Tools/ Parts

Detailed Instructions

Picture/ Illustration

READ FITTING INSTRUCTIONS IN FULL BEFORE INSTALLATION

This article is sold without warranty expressed or implied. No warranty or representation is made as to this product's ability to protect the user from injury or death. The user assumes that risk. The effectiveness, warranty and longevity of this equipment are directly related to the manner in which it is INSTALLED, USED, and/or MAINTAINED. THE USER ASSUMES THE RISK.

By purchasing this product and opening the packaging, purchasers expressly acknowledge, understand and agree that they take, select and purchase these SECTOR 111 products from SECTOR 111, its affiliates, distributors, and agents (collectively, SECTOR 111) **as is** and **with all faults**.

The entire risk as to the quality and performance of these SECTOR 111 parts is with the purchasers. Working on your car can be a dangerous activity. If you are unsure of what you are doing, please leave mechanical or Safety critical work to a skilled mechanic.

We take no responsibility for the incorrect use and/or installation of SECTOR 111 products.

Front Brake Install

1. Pre-install Inspection

- 1 Left Rotor
- 1 Right Rotor
- 1 Left Caliper w/ Brake Pads and Info Packet
- 1 Right Caliper w/ Brake Pads and Info Packet

a. Before you begin installation, confirm all the parts on the list to the left are present.

Assembly Step	Tools/ Parts	Detailed Instructions	Picture/ Illustration
	<ul style="list-style-type: none"> • 1 Left Caliper Bracket • 1 Right Caliper Bracket • 1 Information Packet From Brake Pros • 2 Goodridge Stainless Steel Brake Lines • 4 M10-1.5 x 25mm SHC Screws • 4 M10-1.5 x 40mm SHC Screws • 4 M10 Flat Washers • 4 M10 Narrow Flat Washers • 1 Small Container of Loctite 		
<p>2. Remove Front Wheels</p>	<ul style="list-style-type: none"> • Jack • Jack Stands • 17mm Socket • Breaker Bar 	<ol style="list-style-type: none"> a. Break loose lug bolts. b. Lift and secure the front of the car. c. Remove front wheels. 	

Assembly Step	Tools/ Parts	Detailed Instructions	Picture/ Illustration
---------------	--------------	-----------------------	-----------------------

	<ul style="list-style-type: none">• Lotus Lug Tool and Key		
--	--	--	--

Note: For Exige installs, remove front clam as described in Lotus factory service manual.

Complete, detailed directions are provided in the kit. This is an advanced skilled project.

A list of suggested local installers is available on our website.