

sector 111

proRAD

Rev. A

Page 1 of 4

Assembly Step

Tools/ Parts

Detailed Instructions

Picture/ Illustration

PROFESSIONAL INSTALLATION ONLY

READ FITTING INSTRUCTIONS IN FULL BEFORE INSTALLATION

This article is sold without warranty expressed or implied. No warranty or representation is made as to this product's ability to protect the user from injury or death. The user assumes that risk. The effectiveness, warranty and longevity of this equipment are directly related to the manner in which it is INSTALLED, USED, and/or MAINTAINED. THE USER ASSUMES THE RISK.



By purchasing this product and opening the packaging, purchasers expressly acknowledge, understand and agree that they take, select and purchase these SECTOR 111 products from SECTOR 111, its affiliates, distributors, and agents (collectively, SECTOR 111) **as is** and **with all faults**.

The entire risk as to the quality and performance of these SECTOR 111 parts is with the purchasers. Working on your car can be a dangerous activity. If you are unsure of what you are doing, please leave mechanical or Safety critical work to a skilled mechanic.

We take no responsibility for the incorrect use and/or installation of SECTOR 111 products. These installation directions are intended to be used as a guide only. Professional installation only.

We take no responsibility for the incorrect use and/or installation of SECTOR 111 products.

proRAD

Assembly Step	Tools/ Parts	Detailed Instructions	Picture/ Illustration
Pre-install Inspection	<ul style="list-style-type: none"> • 1 Pro Alloy radiator 	<ul style="list-style-type: none"> • Before you begin installation, confirm the radiator has not been damaged during shipping. 	
1. Drain Coolant			
2. Remove front clam		<ul style="list-style-type: none"> •Please note: This install is highly recommended to be carried out by a professional. Proper removal of front clam and bleeding and testing of system is required. 	

Assembly Step	Tools/ Parts	Detailed Instructions	Picture/ Illustration
---------------	--------------	-----------------------	-----------------------

3. Be careful not to distort or damage cooling passages or side tanks

•Note: Side tanks, mounting flanges, inlet and outlet hoses are aluminum which are fragile my nature. Exercise care in handling. Again, professional installation is required.



Once you are finished and have checked for leaks. Bleed the cooling system according to the Factory Service Manual.

Assembly Step**Tools/ Parts****Detailed Instructions****Picture/ Illustration*****DISCLAIMER OF WARRANTY***

Sector 111 cooling products are sold as Racing and Off-highway equipment. Sector 111 cannot control the end use of the product in regards to proper installation, bleeding of cooling system, and use, and therefore cannot make applicable any expressed warranty or guarantee for any specific period of time.

Sector 111 warrants the radiator as delivered as free from defects in materials and or workmanship while in new, unused condition. Once the product has been mounted to vehicle and-or used in any way, the product is the responsibility of the owner.

Exclusions from warranty of new product: 1.) Improper installation. 2.) Modification or alteration. 3.) Cases of misuse or intentional damage. 4.) In any case where the part or component has been damaged as the result of an accident or impact due to use beyond the intended and normal life of the product.

Any defective Sector 111 product must be returned in the original packaging in unused condition freight pre-paid for inspection. If a product is found to be defective in material or workmanship, it will be replaced and return shipped without charge.

This disclaimer applies to the original purchaser and all other persons as well.